

## Model TT Coupe 3.2 quattro S tronic

Engine type	Six-cylinder spark ignition engine, DOHC
Displacement in cc (valves per cylinder)	3189 (4)
Max. output in kW at rpm	184/6300
Max. torque in Nm at rpm	320/2500-3000

### Power transmission/Wheels

Drive type	quattro® permanent all-wheel drive
Transmission type	6-speed S tronic
Wheels	Lightweight forged aluminium, 9 J x 18
Tyres	245/40 R 18

### Weights/Capacities

Unladen weight <sup>1</sup> in kg	1430
Permitted total weight in kg	1830
Fuel tank capacity, approx. in l	60
Boot capacity, approx. in l	290

### Performance/Consumption

Top speed in km/h	250 <sup>5</sup>
Acceleration 0-100 km/h in s	5.7
Fuel type <sup>3</sup>	Super Plus unleaded 98 RON
Fuel consumption <sup>2</sup> in km/l	10.36 <sup>4</sup>

#### Notes

- Weight of car unladen, without driver (calculated in accordance with the current applicable version of Directive 92/21/EEC). Optional equipment may increase the car's unladen weight and drag coefficient, whereupon the possible payload limit and the top speed will be reduced accordingly.
- A vehicle's fuel consumption do not just depend on how efficiently the vehicle uses the fuel but are also affected by driver behavior and other non-technical factors.
- Recommend using SuperPlus unleaded (98 RON). If this is not available, use super unleaded (95 RON); power output will be slightly reduced.
- The figures given were calculated using the specified measuring procedure (current applicable version of directive 80/1268/EEC). The figures do not refer to one individual vehicle and do not form part of any offer, but rather should be used purely for purposes of comparison between the different vehicle models.
- Electronically limited.

#### Important note

Inspections are due as shown on the service display.

## R8 4.2 FSI quattro

V8 petrol engine with direct fuel injection	V8 petrol engine with direct fuel injection
4163 (4)	4163 (4)
309/7800	309/7800
430/4,500 – 6000	430/4,500 – 6000

## R8 4.2 FSI quattro R tronic

quattro® permanent all-wheel drive	quattro® permanent all-wheel drive
6-speed manual transmission	R-tronic sequential 6-speed transmission
Front - Cast aluminium wheels, 8.5 J x 18 Rear - Cast aluminium wheels, 10.5 J x 18	Front - Cast aluminium wheels, 8.5 J x 18 Rear - Cast aluminium wheels, 10.5 J x 18
Front - 235/40 R 18 Rear - 285/35 R 18	Front - 235/40 R 18 Rear - 285/35 R 18

1560	1565
1860	1865
75	75
100	100

301	301
4.6	4.6
Super Plus 98 RON	Super Plus 98 RON
6.84 <sup>4</sup>	7.35 <sup>4</sup>

#### Notes

- Weight of car unladen, without driver (calculated in accordance with the current with the current applicable version of Directive 92/21/EEC). Optional equipment may increase the car's unladen weight and drag coefficient, whereupon the possible payload limit and the top speed will be reduced accordingly.
- A vehicle's fuel consumption do not just depend on how efficiently the vehicle uses the fuel but are also affected by driver behavior and other non-technical factors.
- Recommend using SuperPlus unleaded (98 RON). If this is not available, use super unleaded (95 RON); power output will be slightly reduced.
- The figures given were calculated using the specified measuring procedure (current applicable version of directive 80/1268/EEC). The figures do not refer to one individual vehicle and do not form part of any offer, but rather should be used purely for purposes of comparison between the different vehicle models.

#### Important note

Inspections are due as shown on the service display.